

BEST SOLUTIONS TO MEET YOUR NEEDS

STEREO MICROSCOPE

Heavy Duty Single Arm Boom Stand-50253 Heavy Duty Double-arm Boom Stand-50259

ASI PN 50259

Viewing head: 45° inclined, 360° rotatable binocular head or rinocular head.

The inter-papillary distance adjustable between 54-75mm;

both diopter adjustment of range $\pm 5 \text{mm}$.

Eyepiece: Wide field, high-eyepoint eyepiece.

Objective: Zoom objective magnification 0.70X-4.5X.

Magnification range: between 3.5X-45X.

Working distance: 100mm, special maximum working distance can provide more

working space for you.

Illumination: Built-in and built-out illumination system





Specification:

Eyepiece	Standard specification		Auxiliary objective 0.5X		Auxiliary objective 1.5X		Auxiliary objective 2.0X	
	Working distance 100mm		Working distance 165mm		Working distance 45mm		Working distance 30mm	
	Magnificatio n	View field	Magnificatio n	View field	Magnificatio n	View field	Magnificatio n	View field
10X/20mm	7.0X	28.6mm	3.5X	57.1mm	10.5X	19mm	14X	14.3mm
	45.0X	4.4mm	22.5X	8.9mm	67.5X	3mm	90X	2.2mm
15X/15mm	10.5X	21.1mm	5.25X	42.8mm	15.75X	14.3mm	21X	10.7mm
	67.5X	3.3mm	33.75X	6.7mm	101.25X	2.2mm	135X	1.7mm
20X/10mm	14.0X	14.3mm	7.0X	28.6mm	21.0X	9.5mm	28X	7.1mm
	90.0X	2.2mm	45.0X	4.4mm	135.0X	1.5mm	180X	1.1mm







STEREO MICROSCOPE

Accessories:

<u>Stand</u>



0.5X Auxiliary objective Lens



1.5X Auxiliary objective Lens



LED light-144 bulb- for microscope



0.75X Auxiliary objective Lens



2.0X Auxiliary objective Lens



