

TMT-9000S

Soldering & Rework Station

**LEAD
FREE**

**ESD
SAFE**



The TMT-9000S is based on Curie Heat Technology which responds to the thermal demands of each solder joint by adjusting the power instantaneously, thereby meeting the exact requirements of the substrate component and solder material.

- High thermal recovery & performance.
- 13.56MHz power supply with built-in LCD display.
- Dual switchable soldering ports.
- No calibration or operator training required.
- No additional coil assembly cost

TMT-9000S SPECIFICATIONS

Input Line Voltage:	TMT-9000PS-1	100-110 VAC
	TMT-9000PS-2	220-240 VAC
Tip to Ground Potential:	2mV, true RMS 50-500Hz	
Tip to Ground Resistance:	<2 Ohms DC	
Idle Temperature Stability:	+/- 1.1°C (2°F)	
Ambient Operating Temperature:	10-40°C (50°F -104°F)	
Maximum Enclosure Temperature:	50°C (122°F)	
Fuse:	TMT-9000PS-1	12250V 0.5A
	TMT-9000PS-2	5V 1A
Output Power (Maximum):	40 Watts RF	
Output Frequency:	13.56 MHz	
Size (W x H x D):	212.4mm x 118mm x 132mm	
Weight:	3.47 KG	
LCD display:	60.0mm x 16.0mm	
Input Line Frequency:	50/60 Hz	

PACKING LIST

TMT-9000PS	Power Supply
SHH-1	Soldering Handpiece Holder
SHP-1	Soldering Handpiece
RMP-1	Tip Removal Pad
SG-1-HRB	Heat Resistant Grip
SG-1-GR	Handpiece Grip Green
SG-1-GY	Handpiece Grip Gray
BC-1	Brass Curls
SPG-1	Sulphide Free Sponge
M7CH176	Soldering Tip Cartridge

M SERIES - TIP CARTRIDGES FOR TMT-9000S



Patented Color Band